

Grating Fasteners
P. O. Box 610
Harvey, LA 70059



Home of "G-Clips"...the best grating fastener

G-Clip Dimensions

		<p><u>Letter to part descriptions:</u></p> <ul style="list-style-type: none"> A: Grip jaw Width B: Grip jaw Steel Thickness C: Grip jaw Length D: Grip jaw Flange Height E: Grip jaw Opening F: Overall Grip jaw Height G: Hole Center to Edge H: Grip jaw Depth I: Top Plate Thickness J: Top Plate Length K: Top Plate Width L: Top Plate Depression Depth M: Hex Head Cap Screw N: Screw Length 	
<p><u>RSSGG-1 Dims:</u></p> <ul style="list-style-type: none"> A: 3/4" B: 13 gauge C: 1-1/8" D: 1/8" E: 13/16" F: 1-3/4" G: 1/4" H: 5/8" I: 16 gauge J: 2-1/8" dia K: 2-1/8" dia L: 1/8" M: 1/4"-20 N: varies 	<p><u>RSSGG-2 Dims:</u></p> <ul style="list-style-type: none"> A: 3/4" B: 13 gauge C: 1-1/8" D: 1/8" E: 1-9/32" F: 2-1/8" G: 1/4" H: 5/8" I: 16 gauge J: 2-1/8" dia K: 2-1/8" dia L: 1/8" M: 1/4"-20 N: varies 	<p><u>RSSGG-3 Dims:</u></p> <ul style="list-style-type: none"> A: 3/4" B: 13 gauge C: 1-1/8" D: 1/8" E: 1-7/8" F: 2-3/4" G: 1/4" H: 5/8" I: 16 gauge J: 2-1/8" dia K: 2-1/8" dia L: 1/8" M: 1/4"-20 N: varies 	<p><u>RSSGG-4 Dims:</u></p> <ul style="list-style-type: none"> A: 3/4" B: 13 gauge C: 1-1/8" D: 1/8" E: 2-3/8" F: 3-1/4" G: 1/4" H: 5/8" I: 16 gauge J: 2-1/8" dia K: 2-1/8" dia L: 1/8" M: 1/4"-20 N: varies

Phone (toll-free) 1-800-227-9013 (504) 361-3471 Fax (504) 362-9059
Internet: www.gclips.com e-mail to: sales@gclips.com